



# LEMSAFESTRIKE

## PREMIUM SAFE MOULD RELEASE AGENT

LEMSAFESTRIKE is blend of natural vegetable oils and other vegetable extracts for general site and precast yard use. It achieves a top quality concrete finish in most situations and with most common mould surfaces. Release is achieved by a combination of the oil forming a physical barrier between the formwork surface and the concrete and is boosted by the release process. Surfactants help to eliminate blowholes and provide a clean uniform and non-stained surface.

### Advantages

- Safe, environmentally friendly product.
- Facilitates easy formwork release.
- Provides uniform stain-free concrete surfaces.
- Minimises incidence of surface air voids.
- Reduces form cleaning to a minimum.
- Highly resistant to removal by rain showers or foot traffic. High coverage rate provides economic usage.
- Suitable for use on all types of formwork in all climatic conditions.
- Easy application by spray, brush or swab.
- Suitable for use with white or standard OPC concrete finishes.
- Suitable for use on sealed or unsealed timber formwork.
- Forms may be stripped early when other factors permit.
- Ideal for achieving release from multi-planed features e.g. trapezoidal ribs, cone shaped column heads etc.
- Fully compatible with the subsequent application of silicone or similar surface treatments when used as recommended.
- NO VOC, Bio-gradable

### Application

After preparation of formwork and any necessary sealing, apply thinly, by spray, brush or swab prior to each concrete pour, and as near to time of placement of concrete as practical conditions permit. Timber and other porous forms which have not been treated with LEMSEAL Plastic Formwork Coating or other suitable sealer should initially be treated with a double coat of LEMSAFESTRIKE, the first applied heavily and allowed to stand for maximum absorption before the second is applied in normal manner. On vertical forms any excess material accumulating at the bottom of the form should be removed.

### Coverage

A thin coating gives a coverage rate of 30 to 50m<sup>2</sup> per litre depending upon surface porosity. The BCA report "appearance matters" states that excessive application of release agents is detrimental to concrete surface finish. Care should therefore be taken to ensure that LEMSAFESTRIKE is applied as recommended as this will achieve optimum performance and maximum economy.

### Storage

No special storage considerations are required as this product is not affected by frost or ambient heat. Shelf life- Practically unlimited in sealed containers.

### Health & Safety

Prolonged physical contact should be avoided and personal and environmental hygiene encouraged in common with the use of all mould release agents. Where contact with skin occurs, the material should be removed with soap and water. If splashes affect eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists medical attention should be sought without delay.

**Southern Division**  
Russell Gardens  
Wickford, Essex SS11 8BH  
T: 01268 571571  
E: wickford@lemon-gs.co.uk

**Midland Division**  
Hunters Lane  
Rugby, Warwickshire CV21 1EA  
T: 01788 571571  
E: rugby@lemon-gs.co.uk

